

FILTERCOR PLEATED POLYESTER

SERIES PE



The chemical and bacteria resistance of the Series PE polyester media makes these cartridges suitable for most light industrial applications, swimming pool and spa, and well water applications. The durable, non-woven polyester fabric is reusable, while being pleated to maximize its dirt holding capacity and extending the time period between changes.

The 2 5/8" diameter by 9 3/4" length has more than 4 ft² of fabric media while the larger 4 1/2" diameter by 9 3/4" long version has more than 16ft².

Specifications

Type: Pleated Non-Woven Polyester

Construction: Non-Woven Polyester Fabric Medi

Vinyl Plastisol End Caps

Polypropylene Core

Polyethylene Outer Sheath

Operating Temperature Range: 40°F (4.4°C) to 125°F (52°C)

Micron Rating: Nominal 1, 5, 10, 20, 30, 50

Dimensions:

- 2 5/8" diam. X 9 3/4", 10" long
- 2 5/8" diam. X 19 1/2", 20" long
- 2 5/8" diam. X 30" long
- 2 5/8" diam. X 40" long
- 4 1/2" diam. X 9 3/4" long
- 4 1/2" diam. X 20" long

Max. Recommended Flow Rates:

- 10 GPM
- 15 GPM
- 20 GPM
- 25 GPM
- 25 GPM
- 40 GPM

Nomenclature

PE	1	X	10	BB
Filter Media	Micron Rating		Length	Tube O.D.
PE- Polyester	1		9 3/4"	All filters are standard 2 5/8" O.D. unless otherwise specified BB - 4 1/2"
	5		10"	
	10		19 1/2"	
	20		20"	
	30		30"	
	50		40"	



7932 Ajay Drive, Sun Valley, CA 91352
(818) 504-9471 FAX:(818) 768-7590