



#### MH09 SERIES MEMBRANE HOUSINGS

- Thicker Body for Stronger Durability
- Stronger, Better Engineered Membrane Cup
- Accepts most Standard Residential Membranes

#### MH09 SERIES MEMBRANE HOUSINGS

#### LIQUATEC MH09 SERIES MEMBRANE HOUSINGS

are manufactured with high-quality NSF approved material. This housing will accommodate most standard membrane elements. Our superiorly designed housing utilizes a FLAT GASKET and an o-ring to ensure a True Double o-ring seal. Where most other membrane housings lacking one o-ring will leak. Our thicker body and stronger membrane cup design eliminates the possibility of cracking while inserting the membrane into the housing. By this you do not have to worry about bypass of Brine water to the Permeate side which is quite common on most other housings manufactured today. Standard 1/8" basic thread port. Optional 1/4" quick connect ports are available. White and Black housings are standard.



#### LIQUATEC MH09 SERIES MEMBRANE HOUSINGS

are Tested and Certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements only.

## MH09 SERIES MEMBRANE HOUSINGS



COMPONENT

Tested and Certified by NSF International to ANSI/NSF Standard 42 for material requirements only.

1/4" QUICK CONNECT FITTING OPTIONAL



### MATERIALS OF CONSTRUCTION

- |                       |                 |
|-----------------------|-----------------|
| • HOUSING             | POLYPROPYLENE   |
| • CAP                 | POLYPROPYLENE   |
| • O-RING              | EPDM            |
| • MAXIMUM TEMPERATURE | 125°F (51.7°C)  |
| • MAXIMUM PRESSURE    | 100 PSI (7 BAR) |

### EXPLODED VIEW



### THICKER WALLS AND STRONGER MEMBRANE CUP

LIQUATEC



OTHERS



DISTRIBUTED BY:

**Liquatec**  
products

P.O. Box 10421 Fullerton, CA 92838 USA  
sales@Liquatec.com  
www.Liquatec.com