

## 5600 ECONOMINDER METERED UNIT - CABINET SERIES

The **5600 Econominder Power head** saves up to 50% on salt and water. Simple and dependable mechanical meter monitors water usage even during power failure and initiates regeneration only when needed.

Model TT Twin Tank  
 Stainless Steel Systems  
 5600 Metered Outdoor / Indoor



Model RT Rectangular  
 Built-in Brine Tank Cabinet  
 5600 Metered Indoor System



**5600 Econominder Valves**

These top quality control valves are available in 24V or 110V. The regeneration cycles are automatic and dependable.

**Valve Body**

Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.

**Proven Reliability**

THOUSANDS are in service in western United States

**Stainless Steel**

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional).

**Poly Glass Tanks**

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

**Compact Space Saving**

The built-in brine tanks cabinet unit for indoor installations. The valve may be installed in various positions for accessibility.

**Limited Lifetime Warranty**

On pressure tanks and brine tanks. There is a full 3 year warranty on parts

**Locally Manufactured by Water Tec of Tucson Inc.**

From only the highest quality components at our facility in TUCSON, ARIZONA.

**Over 40 Year Reputation**

Of immaculate customer service satisfaction, integrity and quality!

	<b>WATER TEC OF TUCSON</b> 4601 S. 3 <sup>RD</sup> AVE. TUCSON, AZ 85714 PHONE (520)790-1512 FAX (520)745-0549
	<b>WATER TEC OF PHOENIX</b> PHONE (602)288-1422 FAX (520)745-0549 <b>WATER TEC OF NEVADA</b> PHONE (702)270-0900 FAX (702)270-4350
WEBSITE: <a href="http://www.water-tec.com">www.water-tec.com</a> E-MAIL: <a href="mailto:questions@water-tec.com">questions@water-tec.com</a> AZ ROC# 098794 / 104403 NV ROC# 0055223	

*Providing service after the sale since 1967.*

---

---

# 5600 M SPECIFICATIONS

---

---

MODEL NUMBER	GRAINS CAPACITY	RESIN SIZE	BRINE TANK	SALT LBS. USED PER REGEN. CYCLE	WATER GAL. USED PER REGEN. CYCLE	FLOW RATE
RT 1035 56M	32,000	10X35	12X24X42	6-8 LBS. *	25 GAL. *	8 GPM
TT 948 56M	32,000	09X48	18X33	8-10 LBS. *	25 GAL. *	8 GPM
TT 1054 56M	48,000	10X54	18X40	8-12 LBS. *	30 GAL. *	10 GPM

**\* DEPENDING ON INDIVIDUAL WATER CONDITIONS.**

**SYSTEM INCLUDES A 3/4" OR 1" BYPASS VALVE**

**SYSTEM IS AVAILABLE IN 24V OR 110V**

**OPERATING PRESSURE IS 40 - 120 PSI @ 34F - 110F**

**OUR SERVICE TECHNICIANS CAN DELIVER  
AND ADD SALT OR POTASSIUM TO YOUR  
SYSTEM ON A SCHEDULED ROUTE !**



*Ask us about SOFTOUCH™ Sodium - free alternative softener pellets !*