



Automatic Water Conditioning Systems



POINT OF ENTRY - FULLY AUTOMATIC WATER FILTER

The P.O.E. Water Filter System eliminates unwanted substances from water. Designed for use with a water softening system or as a point of entry water filter, the P.O.E system is fully automatic and self cleaning. High Grade Granular Activated Carbon removes Chloramines, Chlorine and other Volatile Organic Contaminants from water as it flows through the filter bed. Other filter media is available for specific requirements.

THE POINT OF ENTRY
Automatic Water Filter System
With Fleck 5600 Timered Filter Control
Valve



Fleck 5600 Automatic

Filter Valve - Timed unit for self-cleaning and self-backwashing.

Proven Reliability and Durability

THOUSANDS are in service in western United States.

Poly Glass Tanks

constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

Limited Lifetime Warranty

On pressure tanks and brine tanks. There is a full 3 year warranty on parts.

Locally Manufactured by Water Tec of Tucson Inc.

From only the highest quality components at our facility in TUCSON, ARIZONA.

Over 40 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!

Why settle for anything but the best?

	WATER TEC OF TUCSON 4601 S. 3 RD AVE. TUCSON, AZ 85714 PHONE (520)790-1512 FAX (520)745-0549
	WATER TEC OF PHOENIX PHONE (602)288-1422 FAX (520)745-0549
	WATER TEC OF NEVADA PHONE (702)270-0900 FAX (702)270-4350
WEBSITE: www.water-tec.com E-MAIL: questions@water-tec.com AZ ROC# 098794 / 104403 NV ROC# 0055223	

Providing service after the sale since 1967.

MODELS & SPECIFICATIONS

MODEL NUMBER	TANK SIZE	MEDIA CAPACITY	WATER GALLONS USED PER BACKWASH CYCLE	FLOW RATE
948 POE	09X48	1 CU. FT.	20 GALLONS	8 GPM
1054 POE	10X54	1.5 CU. FT.	38 GALLONS	10 GPM
1354 POE	13X54	2 CU. FT.	42 GALLONS	12 GPM

FILTER MEDIA HIGH GRADE GRANULAR ACTIVATED CARBON *

CONTROL VALVE FLECK 5600 TIMERED FILTER VALVE

ELECTRICAL RATING TIME CLOCK MOTOR IS 24V OR 110V - 60Hz = 2 Watts

WORKING PRESSURE MINIMUM 40PSI - MAXIMUM 120PSI @ 34 F - 110 F

* OTHER FILTER MEDIA IS AVAILABLE FOR IRON REMOVAL, SEDIMENT, ETC.



Providing service after the sale since 1967.